

Novatik®

Interlocking steel roof system



The advantages of a modern system

Novatik - an elegant, solid and efficient roof, suitable for new or renovated buildings.



Technical data

Overall length	1340 mm
Length of cover	1260 mm
With of cover	370 mm
Number of pannels / sqm	2,15 modules
Roof slope	Min 12°
Protection layer	ZnMg 120 g/sqm
Raw material	Steel 0,5 mm;
Coating	Matt finishing – 35 microns
Weight / sqm	approx. 5 kg/sqm

The steel used in the production of the Novatik interlocking roof system is stable, durable and reliable. The steel coated with Colofer® - VoestAlpine registered trademark – is 0.5 mm thick, while the ZnMg coating is of 120gr/sqm. The ZnMg alloy is resistant under salt fog environments and ensures high anti-corrosion protection.

Distinctive Profile

The design of Novatik tiles was created to replicate ceramic tiles, but with a unique shape.

The sizes were especially chosen so that they would generate a series of advantages:

- easy handling and storage;
- reduced storage space;
- low weight transportation means (easy access in the urban areas);
- reduction of installation losses, especially when dealing with complex architect designed roofs.



Low weight

If it's taken into account from the early stage of the project, it leads to substantial savings for the roof truss and the durability of the house.

Solid fastening system


The tile panels are fastened on the roof battens with nails. The installation details are clean and do not require numerous unnecessary accessories. The roof fastening system and the perfect overlapping of the panels turn Novatik roof into one of the best systems available on the market.

Easy mounting

The model is symmetric and allows for the overlapping of panels in both directions (from left to right or from right to left), facilitating easy installation and reducing the installation time.

Accessories

Novatik offers a full range of roof accessories. The correct use of the accessories ensures perfect roof ventilation and sealing and also adds to its aesthetics.



Side (wall) flashing



Box Barge



Eaves Flashing



Barrel Trim



Valley



Vent



Sanitary vent



Snow guards



Snow stoppers

Warranty

The protection offered by the ZnMg coating ensures high corrosion resistance and superior performance in various environments as compared to the galvanized steel. If the installation is correctly performed, we offer a system with **warranty of 30 years**.

You can enjoy a safe, secure roof for a long period of time.

